

**221213****Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape**

Dimensions

Nominal Size	1-1/4 in 1-5/8 in 1/2 in 1/4 in 2-1/4 in 3/8 in 5/8 in 7/8 in
--------------	---

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	Four 1/2 in–7/8 in Twelve 1/2 in–1/2 in Twelve 1/2 in–7/8 in to device Two 1/2 in–2-1/4 in
Harmonized System (HS) Code	854420 (Coaxial cable and other coaxial electric conductors)
Includes	One roll of 2 in PVC tape Six rolls of 2-1/2 in butyl rubber tape Two rolls of 3/4 in PVC tape
Material Type	Butyl rubber tape PVC tape
Ordering Note	CommScope® standard product (Global)
Package Quantity	1

Mechanical Specifications

UV Resistance Test Method	Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F PVC tape test method UL 510, ASTM D1000
UV Resistance, minimum with no degradation	=1000 hours
Weather Resistance Test Method	04AS00-03.6.0 MIL-STD-1344A, Method 1002

Packed Dimensions

Height	19.6 cm 7.7 in
Length	9.6 cm 3.8 in
Shipping Weight	1.52 kg 3.35 lb
Width	17.4 cm 6.9 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
China RoHS SJ/T 11364-2006	Below Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



221213

Included Products

42615-10 — Butyl Rubber Tape, 24 in

9905-41 — Black 3/4 in PVC Tape, 66 ft

9905-71 — Black 2 in PVC Tape, 20 ft