



245171

Andrew 3M™ Cold Shrink™ Kit for 7/8 in to 1/4 in through 1/2 in connections

Dimensions

Nominal Size	1/2 in 1/4 in 7/8 in
Cable Diameter for Seal, maximum	21.34 mm 0.84 in
Cable Diameter for Seal, minimum	7.37 mm 0.29 in
Inner Diameter	51.31 mm 2.02 in
Length	254.00 mm 10.00 in
Width	53.85 mm 2.12 in

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	One 1/4 in–1/2 in to 7/8 in
Color	Black
Includes	One EPDM rubber tube One sealing foam strip
Material Type	EPDM rubber
Ordering Note	CommScope® non-standard product
Package Quantity	1

Mechanical Specifications

UV Resistance Test Method	UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp
UV Resistance, minimum with no degradation	=1000 hours
Weather Resistance Test Method	04AS00-03.6.0 MIL-STD-1344A, Method 1002

Packed Dimensions

Height	30.0 cm 11.8 in
Length	4.6 cm 1.8 in
Shipping Weight	0.18 kg 0.40 lb
Width	7.0 cm 2.8 in

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU
China RoHS SJ/T 11364-2006
ISO 9001:2008

Classification

Compliant
Below Maximum Concentration Value (MCV)
Designed, manufactured and/or distributed under this quality management system

