

# LIGHTWEIGHT PADDED

## **HEADSET**



The **Lightweight Padded headset** sets the standard in performance, reliability and durability for lightweight headsets. The headset allows for high clarity, discreet two-way radio communications. Comfortable lightweight padding delivers additional comfort necessary for extended wear and is ideal for users working in active, moderate noise environments. An in-line push-to-talk option is also available.

### **Mechanical Specifications:**

- Cable pull from ear cup and mic/PTT, axial: 10 lbs
- Cable pull from T module, axial: 30 lbs
- 24 month manufacturer's warranty

### **Electrical Specifications:**

• Microphone sensitivity at 94dB SPL: -37 typical

### **Environmental Specifications:**

- Operating temperature: -30° C to +75° C
- Storage temperature: -40° C to +85° C

### Be clear, stay connected.

Visit www.ottoexcellence.com or call toll-free 888-234-OTTO (6886) or direct 1-847-428-7171.



# OTTO LIGHTWEIGHT METAL **HEADSET**



The Lightweight Metal headset allows for high clarity, discreet two-way radio communications. Adjustable wire headband fits easily and nearly imperceptibly to the head, allowing the wearer complete freedom of movement.

### **Mechanical Specifications:**

- Cable pull from PTT, axial 20 lbs
- Cable pull from ear cup, axial: 30 lbs
- Cable pull from plug, axial: 40 lbs
- 24 month manufacturer's warranty

### **Electrical Specifications:**

• Microphone sensitivity at 94dB SPL: -45 typical

#### **Environmental Specifications:**

- Operating temperature: -20° C to +60° C
- Storage temperature: -40° C to +80° C